



PROVIDE WITH 4" DEEP SEALED TRAP AND TRAP


PRIMER FITTING OR PROSET TRAP GUARD.


FLOOR SINK DETAIL SCALE: N.T.S.

SCALE: N.T.S.











## **ABBREVIATIONS**

A/E	ARCHITECT/ENGINEER
AF	ABOVE FLOOR
AHU	AIR HANDLING UNIT
APPROX	APPROXIMATE
CU	COPPER, CONDENSING UNIT
CW	DOMESTIC COLD WATER
D	EQUIPMENT DRAIN
DCO	TWO-WAY GRADE CLEANOUT
DEG	DEGREES
DSN	DOWNSPOUT NOZZLE
(E)	EXISTING
EQUIP	EQUIPMENT
EWC	ELECTRIC WATER COOLER
°F	DEGREES FAHRENHEIT
FCO	FLOOR CLEANOUT
FCU	FAN COIL UNIT
FD	FLOOR DRAIN
	CONNECTION INTO EXISTING

FS	FLOOR SINK
FT.	FOOT, FEET
G	NATURAL GAS
GCO	GRADE CLEANOUT
Н	HEIGHT
HB	HOSE BIBB
HP	HORSEPOWER
HW	DOMESTIC HOT WATER
HWC	DOMESTIC HOT WATER
	CIRCULATION LOOP
HWTM	HOT WATER TEMPERATURE
	MAINTENANCE CABLE
HZ	HERTZ
ΙE	INVERT ELEVATION
IN.	INCH, INCHES
J-BOX	JUNCTION BOX
kW	KILOWATT
L	LENGTH

	LB	POUNDS
	LRA	LOCKED ROTOR AMPS
	MAX	MAXIMUM
	MCA	MINIMUM CIRCUIT AMPACITY
	MIN	MINIMUM
	MS	MOP SINK BASIN
	N/A	NOT APPLICABLE
	NFPA	NATIONAL FIRE PROTECTION
		ASSOCIATION
DE	NFWH	NON-FREEZE WALL HYDRANT
RE	N/O,N/C	NORMALLY OPEN, NORMALLY CLOS
	O/C	ON CENTER
	PCO	PLUG CLEANOUT
	PH	PHASE
	PROVIDE	FURNISH AND INSTALL

POUNDS PER SQUARE INCH

FOR TWO OR MORE

PIPES

2. HANGER RODS SHALL BE OF THE SAME SIZE

PIPING (WITHOUT INSULATION AND SADDLES.)

P-3 / SCALE: N.T.S.

REQUIRED, BUT NOT SMALLER THAN 1/2" DIAMETER.

3. HANGERS ARE ALSO TYPICAL FOR UNINSULATED

PIPE SUPPORT DETAIL

	RD	ROOF DRAIN
	RE:	REFERENCE, REFER
	RLA	RUNNING LOAD AMPS
	RM	ROOM
	RPBP	REDUCED PRESSURE
		BACKFLOW PREVENTER
	S	SINK
	THRU	THROUGH
	TP	TRAP PRIMER
	TYP	TYPICAL
	UR	URINAL
D	UL	UNDERWRITERS LABORATORIES, INC.
.0	V	SANITARY VENT
	VTR	SANITARY VENT THRU ROOF
	W	SANITARY DRAINAGE
	WC	WATER CLOSET
	WCO	WALL CLEANOUT
	W/	WITH
	WHA	WATER HAMMER ARRESTER

-INSULATION STEEL SHIELD

~INSULATION

ANGLE

STEEL SHIELD

CONCRETE SURFACE OR FLOOR COVERING AS REQUIRED

FLOW

FINISHED FLOOR CLEAN-OUT DETAIL

THREADED ROD

CLEVIS TYPE

1/2" DIA. MIN. ROD

GALVANIZED SHEET —

LENGTH THREE TIMES

PIPE DIA. - MIN. 9"

1. INSULATION ABOVE SADDLES SHALL BE FOAM GLASS OF SAME THICKNESS AS

PIPE INSULATION AND COMPRESSIVE STRENGTH OF NOT LESS THAN 3,300 PSI.

- INSULATION -

HANGER

1/8 BEND

FOAM GLASS — INSULATION ABOVE

SADDLE-NOTE 1

18 GAGE GALV.—

PIPE SADDLES

SHEET MTL.
INSULATION STEEL
SHIELD — NOTE 1

18 GAGE GALV.—

INSULATION STEEL

SHIELD - NOTE 1

INSULATION ABOVE

3"x3"x1/4"

ANGLE

SADDLE-NOTE 1

SHEET MTL.

FOAM GLASS

NOTES:

P-3 SCALE: N.T.S.

- CLEANOUT COVER


- CLEANOUT PLUG

CAULKING FERRULE

CONCRETE ANCHOR

\_\_\_\_ 24" X 24" X 24"

- CSK SCREW



## LINE TYPES

ARCHITECT

PARKER

<u>a</u>

FRED


 $\forall$ 

 $| \bigcirc \square$ 

P.O. BOX 1016 TEXAS 76401


SANITARY DRAINAGE
GREASY WASTE
EQUIPMENT DRAIN
ROOF STORM DRAINAGE
SECONDARY ROOF DRAIN
SUB-SURFACE DRAINAGE
SANITARY VENT
DOMESTIC COLD WATER
DOMESTIC HOT WATER
DOMESTIC HOT WATER CIRCULATION
NATURAL GAS
FIRE PROTECTION
DIRECTION OF FLOW
DIRECTION OF PIPE SLOPE DOWN
PIPE DEMOLITION

## VALVES AND FITTINGS



DCC	TVVO VVAT CLLANOUT
GCO	GRADE CLEANOUT
× */	NON-FREEZE WALL HYDRANT OR HOSE BIBB
FD	FLOOR DRAIN
FCO	FLOOR CLEANOUT

CONNECT NEW TO EXISTING



MULTI RANG[ 23C09R,  $\sim$ nformation shown, in whole or in part, without SE's consent, is strictly prohibited, is a copyrigh breach and may be prosecuted. Any unauthorized reuse shall be at the sole risk of the use